

CLEARING AND GRUBBING

STATION TO STATION	NO. OF STATIONS CLEARING	NO. OF STATIONS GRUBBING
7+50 - 11+38.46	3.0	3.0

CRUSHED AGGREGATE BASE COURSE

STATION TO STATION	LOCATION	C.Y.
7+50 - 11+38.46	MAINLINE	300
7+50 - 11+38.46	LEFT SHOULDER	100
7+50 - 11+38.46	RIGHT SHOULDER	150
TOTAL		550

SIGNS, TYPE II, REFLECTIVE, & WOOD POSTS

STATION	LOCATION	SIGN	S.F.	WOOD POSTS 4X4-INCH X 10 FEET
9+74	END OF STRUCTURE LT	W5-52L	3	1
9+60	END OF STRUCTURE RT	W5-52R	3	1
10+40	END OF STRUCTURE LT	W5-52R	3	1
10+26	END OF STRUCTURE RT	W5-52L	3	1
TOTAL			12	4

SILT FENCE

STATION	LOCATION	DELIVERED L.F.	INSTALLED L.F.	MAINTENANCE L.F.
7+50 - 10+00	LT & RT	500	500	1000
10+10 - 11+38	RT	200	200	400
10+10 - 11+38	LT	100	100	200
TOTAL		800	800	1600

SAWING EXISTING PAVEMENT

STATION	L.F.
207+25 - 210+00	275
7+50	20
TOTAL	295

ASPHALTIC SURFACE, SPECIAL

LOCATION	S.Y.
SPIRIT FALLS AVE	900

PIPE UNDERDRAIN, 6-INCH

STATION	L.F.
9+67	50
10+33	50
TOTAL	100

GEOTEXTILE FABRIC, TYPE MS

STATION	LOCATION	S.Y.
7+50	MAINLINE LT	537
10+00 - 11+00	MAINLINE LT	313
TOTAL		850

GEOTEXTILE FABRIC, TYPE DF

STATION	LOCATION	S.Y.
9+67	PIPE UNDERDRAIN	35
10+33	PIPE UNDERDRAIN	35
TOTAL		70

TURBIDITY BARRIER, 4-FOOT

LOCATION	DELIVERED L.F.	INSTALLED L.F.
SOUTH ABUTMENT	110	110
NORTH ABUTMENT	160	160
TOTAL	270	270

EROSION CONTROL

STATION TO STATION	LOCATION	TOPSOIL S.Y.	MULCHING S.Y.	FERTILIZER TYPE B CWT.	SEEDING NO. 10 LBS.	SEEDING WETLANDS NO. 60 LBS.	SALVAGED WETLAND TOPSOIL S.Y.
7+50 - 11+38.46	SPIRIT FALLS AVE	1750	2200	1.5	30	---	---
	BORROW PIT	---	---	1.5	30	---	---
	WETLAND	---	---	---	---	10	170
TOTAL		1750	2200	3.0	60	10	170