



CROSS SECT. THRU RDWY.

ALL SURFACES OF PRESTRESSED GIRDERS THAT WILL BE WITHIN THE LIMITS OF THE ABUTMENT CONCRETE DIAPHRAGM SHALL BE COATED WITH PARAFFIN WAX.

TOTAL ESTIMATED QUANTITIES

| BID ITEMS | UNIT | SOUTH ABUT. | NORTH ABUT. | SUPER. | TOTALS |
|--|------|-------------|-------------|--------|-------------|
| REMOVING OLD BRIDGE, STA. 20+00 | L.S. | ---- | ---- | ---- | 1 |
| EXCAVATION FOR STRUCTURES, BRIDGES B-XX-XX | L.S. | ---- | ---- | ---- | 1 |
| CONCRETE MASONRY, BRIDGES | C.Y. | ---- | ---- | ---- | ---- |
| HIGH STRENGTH BAR STEEL REINFORCEMENT, BRIDGES | LB. | ---- | ---- | ---- | ---- |
| COATED HIGH-STRENGTH BAR STEEL REINF., BRIDGES | LB. | ---- | ---- | ---- | ---- |
| PROTECTIVE SURFACE TREATMENT | GAL. | ---- | ---- | ---- | ---- |
| CAST-IN-PLACE CONCRETE PILING, DELIVERED AND DRIVEN, 10 3/4-INCH | L.F. | ---- | ---- | ---- | ---- |
| PRESTRESSED GIRDER, I TYPE, 36-INCH | L.F. | ---- | ---- | ---- | ---- |
| NON-LAMINATED ELASTOMERIC BEARING PADS | EA. | ---- | ---- | ---- | ---- |
| TUBULAR RAILING, TYPE F, STRUCTURE B-XX-XX | L.S. | ---- | ---- | ---- | 1 |
| HEAVY RIPRAP | C.Y. | ---- | ---- | ---- | ---- |
| GEOTEXTILE FABRIC, TYPE HR | S.Y. | ---- | ---- | ---- | ---- |
| GEOTEXTILE FABRIC, TYPE DF | S.Y. | ---- | ---- | ---- | ---- |
| NON-BID ITEMS | | | | | |
| PREFORMED JOINT FILLER | SIZE | ---- | ---- | ---- | 1/2" & 3/4" |
| POLYVINYL CHLORIDE WATERSTOP | L.F. | ---- | ---- | ---- | ---- |

| | | | |
|--|------|---------------|-------------------|
| NO. | DATE | REVISION | BY |
| STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION | | | |
| STRUCTURE B-XX-XX | | | |
| CONST. SPEC. | 1989 | DRAWN BY OMNI | PLANS CHECKED JWT |
| GENERAL PLAN | | | SHEET 2 OF 8 |
| | | | X |