



- LEGEND**
- ① CONCRETE CURB & GUTTER 6" MOUNTABLE 36" TYPE D
 - ② CONCRETE CURB TYPE J
 - ③ ASPHALTIC SURFACE DRIVEWAYS & FIELD ENTRANCES
 - ④ BASE AGGREGATE DENSE 1 1/4-INCH
 - ⑤ ASPHALTIC FLUME
 - ⑥ ASPHALTIC SURFACE SAFETY ISLAND
 - XXXX SAWING EXISTING PAVEMENT

NOTE
ALL RADII SHOWN TO FLANGE OF CURB UNLESS OTHERWISE NOTED.



111+66.02, 63.71' LT =
599°SM" + 33.83, 15.00' RT
1314.25

R 40'
111+27.70
58.00' LT

111+27.70
18.00' LT
1313.00

111+96.49, 64.23' LT =
599°SM" + 37.56, 15.24' LT
1314.18

R 60'
112+54.88
78.00' LT

112+54.88
18.00' LT
1312.14

STA 111+86.10.00 =
STA 600°SM" + 00.00
TYPE "D" INTERSECTION REQ'D

PAVE SHOULDER FULL WIDTH
THROUGH DRIVEWAY (SEE CONSTRUCTION DETAIL)

REMOVE DRIVEWAY,
GRADE, TOPSOIL, &
SEED AREA