

SECTION
RANDOM LINES

106	105	104	88	87	90						
6	65	5	89	4	103	3	93	2	74	1	75
83	85	86	92	91	73						
7	66	8	102	9	97	10	94	11	72	12	71
84	107	98	96	63	62						
18	67	17	95	16	78	15	70	14	61	13	2
82	77	76	68	48	1						
19	55	20	52	21	69	22	81	23	60	24	3
99	64	43	59	58	79						
30	54	29	42	28	44	27	80	26	56	25	4
41	40	47	46	45	57						
31	50	32	39	33	51	34	53	35	49	36	5
11	10	9	8	7	6						

SECTION
RANDOM LINES
T 32N

	11		10		9	
101	6	36	5	38	4	12
	34		33		37	
100	7	35	8	32	9	13
	30		31		29	
21	18	27	17	24	16	14
	23		22		25	
20	19	26	20	28	21	15
	18		17		16	
19						

STATE OF WISCONSIN)
Lincoln County) ss

I, Francis Fox, a competent surveyor residing in the City of Merrill, Lincoln County, Wisconsin, hereby certify that the annexed comprises the correct and full minutes of the survey of the Town of Rock Falls, Lincoln County, Wisconsin, made by me pursuant to written contract with the Town Board of the said Town of Rock Falls; that said survey was made by contract with the Town Board of the Town of Rock Falls pursuant to the resolution adopted at the annual 1940 meeting of said town; that before making such survey, I made, executed, and filed a bond to the town in the sum of Three Thousand Dollars (\$3000.00) with sufficient securities and which were approved by the board conditioned that I make a correct and true survey of all the sections in said town and cause land marks to be set permanently at the section and quarter section corners as established by the United States Survey and that I faithfully perform such work and the duties imposed upon me according to law.

I further certify that the annexed minute book gives exact bearings and distances of each monument so set or lo-

cated from each other monument nearest to it or any line in said town; that such land marks were, in all cases possible, set on section corners and corner posts set by the United States survey and that in those cases where there was no reliable evidence by which said corner could be identified that I reestablished the corner posts under the rules adopted by the general government in the survey of public lands and that all such reestablishments and relocations are set forth in the within minutes.

Francis X. Fox
Surveyor

Dated at Merrill, Wisconsin, this 1st day of April, 1943.

FIELD NOTES OF THE TOWN OF ROCK FALLS
BASED ON A DEPENDENT SURVEY THEREOF.
JUNE 1, 1940

SURVEY PARTY

- Francis Fox
- Edward Kaufman
- George Vaughan
- Leslie Vaughan
- Elmer Nicklaus
- Lawarence Guerin

East Bet. 13-24

000 Set sec. corners 13-14-23-24 at
intersection of roads. Set iron
offset stake east 24.75'. Var. 2° 00'

1332.2 Set west 1/16 iron south 6.7'

1770 Enter swamp brs. N-S

1860 Leave swamp

2528 Enter swamp

346.45 Set 1/4 stone south 13.4 in swamp
69' SW to leave swamp
Tamrac 6" S38E 53.0'
Tamrac 5" West 41.5'
Mounded with stone

3969.7 Set east 1/16 south 20.1' in cedar
and ash swamp

4980 Leave swamp

5010.7 Centerline of R.R. track NE-SW

5219.1 Turned rt. SE off ford. tan. to
old stone corner 78.9 20° 32"
to a point 0.9' south of stone

NORTH BET. 13-18

Var. $1^{\circ} 30'$

000	0.9 south of corner
348	Centerline of R.R. track
1337.35	Set 1/16 iron west 3.4' offset iron pipe north 24.75' (1/16 corner at intersection of roads)
2674.7	Old stone $\frac{1}{4}$ corner west 6.8'
3994.7	Set 1/16 corner east 0.8' offset iron pipes E-W 24.75'
5302.3	Turned rt. off ford. tan. NE $34^{\circ} 15'$ 15.0' to section corner stone at inter- section of roads. Off set irons SE-SW 34.9'

SOUTH BET. 19-24

Var. 3°00'

000	0.9' south of corner stone
440	Enter swamp
585	Leave swamp
1314.8	Set 1/16 corner west 7.95 at fence corner
2632.8	Old $\frac{1}{4}$ stone west 15.9'
2631.7	Offset west 29.4'
3855	Enter swamp
3961.75	Set 1/16 east 14.45' in swamp at south edge
3970	Leave swamp
4970	Enter swamp
5284.8	Turned left SE off ford, tan. 79°18' 16.6' to corner stone (old) leave swamp

SOUTH BET. 25-30

000 Sta. 5284.8 bet. 19-24
170 Enter swamp
312 Leave swamp
1304.45 Set 1/16 corner east 105.75'
2618.6 Turned rt. NE off back tan. to $\frac{1}{4}$ stone
set as identified by road and fence
line $85^{\circ}27'$ 197.3'. Offset irons N-S
24.75'

000 $\frac{1}{4}$ stone Var. $1^{\circ}30'$
560 Enter swamp
1220 Leave swamp
1293.45 Set 1/16 corner east 78.95'
2683.95 Turned rt. NE off back tan. $58^{\circ}23'$
185.4' to old corner stone in marsh

SOUTH BET. 31-36

Var. $3^{\circ}30'$

000 Sec. corner stone.
 285 Leave swamp.
 1323.5 Set 1/16 iron west 40.2'.
 2200 Enter swamp.
 2400 Leave swamp.
 2578.9 Turned rt. off ford. tan. SW $49^{\circ}55'$
 105.9' to old $\frac{1}{4}$ stone.

 000 $\frac{1}{4}$ stone. Var. $3^{\circ}30'$
 200 Creek 4' wide flows west.
 687.8 Offset west 44.9'
 1322.55 Set 1/16 iron east 10.8
 1778.7 Offset west 64.7'
 2658.8 Turned rt. NE $73^{\circ}11'$ 47.5' off
 back tan. To old sec. corner stone
 at centerline of road and fence line.
 Stone know to have been removed many
 years ago. Upon digging found point
 of old stone broken off. Set new
 stone 1' beneath top of road. Offset
 iron pipes N-S 24.75'
 (New stone is of black granite)

WEST BET.36-1 T32-T33

Var. 5°

- 000 Town corner
- 1325.15 Set 1/16 corner north 13.75' on north shoulder of road. Offset iron stake south 24.75'
- 1586.4 Offset north 24.5'
- 2650.3 Set 1/4 stone north 3.05' at centerline of road on fence line. Offset iron pipe south 24.75'
- 3976.05 Set 1/16 north 11.6' One foot below top of road in small swamp. Offset iron pipe north 24.75'
- 4001.8 Offset north 26.1
- 4331 Centerline of creek 16' wide flows south.
- 4620 Centerline of R.R. track
- 5327.4 Turned rt. SE off back tan. 13°00' 26.3' to intersection of roads and set section corner stone one foot below top of road. Set iron offsets S45W & N45E 35.0'

WEST BET. 2-35

Var. 3° 50'

000	Sec. corner stone.
1321.6	Set 1/16 north 0.3' - 18' north of the centerline of road in middle of swamp.
2643.3	Set $\frac{1}{4}$ stone north 0.65' four feet south of centerline of road 12" below top of road (gray granite stone) offset iron pipe north 24.75'
3964.9	Set 1/16 corner north 1.0'. North to centerline of road 14.0'
4500	Enter swamp
5140	Leave swamp
5286.55	Set sec. corner north 1.3' by prop- ortionate measurement in south ditch of old road. Set stone flush with ground and mounded with stone. Offset irons N-S 24.75'
5305.5	End of random line.

WEST BET. 3-34 T32-33

000 5305.5 on random line bet. 2-35
 330 Enter swamp
 1000 Leave swamp
 1302.7 Set 1/16 corner north 1.6'
 2100 Enter swamp
 2275 Leave swamp
 2624.3 Set 1/4 stone north 1.95'
 11' east to leave swamp
 Pine 12" N40E 20.8'
 Pine 9" N40W 28.3'
 Mounded with stone.
 2630 Enter swamp
 2828 Leave swamp
 3945.9 Set 1/16 corner north 2.3'
 5105 Enter swamp
 5253.7 Turned rt. of ford. tan. to very old
 corner and set stone NW 10°32' 14.2'
 Ash 11" N30E 12.8'
 Ash 8" S65W 13.2'
 Ash 10" N42W 20.5'
 Ash 12" S49 E 36.0'
 Mounded with sand.
 43' north to leave swamp

WEST BET. 4-33 T32-33

000 5253.7 on random line bet. 3-34
 115 Leave swamp
 1337.4 Set 1/16 corner 0.3'
 2660.9 Set $\frac{1}{4}$ stone south 2' at fence corner.
 Old stumps correspond to original
 witnesses.

Birch 8" S66E 30.8'

3740 Enter swamp
 3991.55 Set 1/16 corner north 4.45'
 4015 Leave swamp
 4640 Centerline of creek flows NW
 4835 Leave creek
 5281.1 Turned rt. off ford. tan. $27^{\circ}18'$
 23.7 to intersection of roads and
 set stone one foot below top of
 road. Offset iron east 24.75.

10

WEST BET. 5-32 T32-33

000	5281.1 on random line bet. 3-34
1320	Creek flows south
1350.1	Set 1/16 corner north 3.55'
	Offset irons N-S 24.75'
2679.1	Set 1/4 corner south 3.8' at centerline of road and fence line
	Offset iron pipe south 24.75'
3770	Enter creek
3815	Leave creek flows SW
4023.6	Set 1/16 corner south 13.2'
4378	Creek flows NW
4386	Leave creek
5313.0	End of random line

WEST BET. 6-31

000 5313.0 on random line bet. 5-32
 55.1 Set section corner stone south
 22.65'
 White tree planting marker 8"
 N20W 51.0'

1399.6 Set 1/16 corner south 32.1'
 2720 Creek flows south
 2744.1 Set $\frac{1}{4}$ stone south 41.5' as witnessed by
 by creek. 10 lks. east of creek
 Elm 20" S61E 29.5
 Mounded with stone

2770 Leave creek
 2870 Centerline of power line
 4088.6 Set 1/16 stone south 50.9
 4314 Centerline of highway CC
 4361.7 Offset south 152.5' to triangulate
 river. On offset turned 70 40'
 bet. hubs on random

4470 Entered Wisconsin river
 4770 Leave river
 4794.9 Hub used in triangulating across
 river

4850 Enter cedar swamp
 5622.3 Turned left SW off ford. stan. to
 stone at original section corner
 32°57' 114.8' on steep slope

Hemlock 15" S40E 19.1
 Cedar 22" N64E 46.5

Terraced and mounded with stone
 Original BT. one degree NE 31.7'

SOUTH BET. 3-4 T32N

000 Section corner
395 Leave swamp
1160 Enter swamp
1619.5 Set 1/16 corner east 6.95'
1485 Leave swamp
2937.7 Set $\frac{1}{4}$ stone east 12.6

Elm 6" N41W 37.9'
Elm 5" N19E 18.4'
4255.9 Set 1/16 corner east 18.3
5558.4 Turned left SE off ford. tan. to
section corner 28.8' at centerline of
road on fence line. Offset pipe south
24.75'

SOUTH BET. 9-10

T32N

000 5558.4 On random line bet. 3-4
 1332.4 Set 1/16 corner east 20.9'
 2649.4 Set 1/4 stone east 17.8'

 Elm 7" N35E 21.0'

 3501 Creek 10' wide flows east
 3770 Enter ash swamp
 3966.4 Set 1/16 corner east 14.6'
 4090 Leave ash swamp
 4550 Creek 15' wide flows west
 5270 Enter swamp
 5283.7 Set section corner stone 9-10-15-16
 east 11.4'

 Pine stump 48" N72E 15.2
 (not marked)

 Mounded with stone

 5312.0 End of random line

SOUTH BET. 15-16 T32N

000 5312.0 On random line bet. 9-10
200 Leave swamp
1288.7 Set 1/16 east 8.2
2605.7 Original corner east 5' remains of
old stumps correspond to original
witnesses. Old iron pipe in place.
Mounded with stone
3924.15 Set 1/16 corner west 1.9'
5237.8 Turned right SW off ford. tan. 10.1'
61°30' to stake set from original
hemlock B.T. NE scribe marks visible
on butt of log. Set section corner
stone at original corner at break in
slope of the ground; slopes down to
the north. Nothing to witness mounded
with stone.

SOUTH BET. 21-22 T32N

000 5237.8 On random bet. 15-16
 1065 Enter swamp
 1325.15 Set 1/16 corner west 28.1'
 1545 Leave swamp
 1940 Enter swamp
 2120 Leave swamp
 2355 Enter swamp
 2530 Leave swamp
 2645.3 Set $\frac{1}{4}$ stone west 47.4'
 nothing to witness
 2970 Enter east edge of swamp
 3070 Leave east edge of swamp
 3965.55 Set 1/16 corner west 66.7
 3981 Fence 101.5' west
 5269.6 Turned right SW off ford. tan $79^{\circ}19'$
 87.6' to road intersection and set
 section corners 21-22-27-28
 Pipe N45E 30'
 Pipe S45W 30'

16

WEST BET. 21-28 T32N

000 Section corner stone
1328.9 Set 1/16 corner south 3.55' offset
iron south 24.75'
1635 Enter creek
1650 Leave creek
2656.8 Set $\frac{1}{4}$ stone south 7.1' in clearing
Set stone flush with the ground
3200 Enter swamp
3655 Leave swamp
3985.7 Set 1/16 corner south 10.65
5278.2 Turned left SW off ford. tan. to
original corner identified by old
pine B.T. Hemlock stump corresponds
to original $21^{\circ}55' 38.1'$
Set stone corners 20-21-28-29
Pine stump 18' S14W 31.4'
S. power pole N43W 46.8'
Mounded with stone.

WEST BET. 20-29 T32N

000 5278.2 On random line bet. 21-28
 145 Enter swamp
 600 Leave swamp
 1347.7 Set 1/16 corner south 15.45' at
 edge of clearing for pole line
 2660.0 Set $\frac{1}{4}$ stone south 16.7 between
 two hills bearing SW-NE at swampy
 narrows
 Maple 7" S6E 12.1
 Maple 7" S7W 9.5
 Mounded with stone
 3080 Enter swamp
 3625 Leave swamp
 3972.4 Set 1/16 corner south 17.95'
 5095 Enter swamp
 5260 Leave swamp
 5266.2 Turned left SW off ford. tan. to
 section corner at centerline of
 road and fence 46°02'26.6'
 Set section corners 19-20-29-30
 one foot below top of road. Offset
 iron east 24.75'

WEST BET. 19-30 T32N

000 5266.2 On random line bet. 20-29
 1338.55 Set 1/16 corner south 12.65' at
 fence line.
 2658.7 Set $\frac{1}{4}$ stone south 6.1' at fence
 corner

 Pine stump 14" N47W 13.8'
 Mounded with stone

 2825 Enter swamp
 3035 Leave swamp
 3145 Enter swamp
 3365 Leave swamp
 3777.6 Centerline of blacktop road 6' north
 to road intersection
 3985.0 Set 1/16 corner north 0.95' offset
 iron south 24.75'
 5560.5 Set section corners 19-24-25-30 north
 .3' as identified by road and fence line.
 Offset irons N-S 24.75'

 1663' west to Wisconsin River

SOUTH BET. 25-30 R5- R6 T32

000 Section corner stone 19-24-25-30
2630.7 Iron stake for $\frac{1}{4}$ corner set in
previous survey west 12.8'
3952.1 Turned left NW off back tan. to
old 1/16 iron $57^{\circ}46'9.6''$
(100'' south to river)

NORTH BET. 19-24 R5-R6 T32

000 5560.5 On rand. line bet. 19-30
1335.45 Set $\frac{1}{16}$ corner west 2.7'
2661.6 Set $\frac{1}{4}$ stone west 5.4' near fence
corner. Mounded with stone
3987.75 Set $\frac{1}{16}$ corner west 8.1'
5313.9 Set section corners 13-18-19-24
at very old stake west 10.8'

Maple	5"	N84W	48.3'
Oak	6"	S80E	33.3'

NORTH BET. 13-18 R5-R6 T32

000	5313.9	On rand. line bet. 19-24
1040		Centerline of road
1319.67		Set 1/16 corner west 17.05'
2340		Enter river
3083		Leave river
3959.0		Set 1/16 corner west 29.55'
5278.7		Set section corners 7-12-13-18 west 35.75'
5281.5		End of rand. line

EAST BET. 17-20 T32 R6

000 Section corner stone 17-18-19-20
set at intersection of roads one
foot below top of road. Offset
iron east 24.75'

1305.15 Set 1/16 corner north 18.8'.
20' north of fence

1595 Enter swamp

1810 Leave swamp

2668.8 Turned right NW off back tan. $32^{\circ}43'$
69.6' to original $\frac{1}{4}$ corner and set
stone

Tamarac	N50W	29.2'
Tamarac	N46E	30.8'

Mounded with stone at south edge
of swamp

3730 Enter swamp

3855 Leave swamp

3917.1 Set 1/16 corner north 58.9'

5223.9 Set section corners 16-17-20-21
north 80.2! Nothing to witness.
Mounded with stone on south side of
hill at toe of slope.

5224.9 End of random line

WEST BET. 18-19 T32

Var. 1°E

000	Section corner stone
1321.9	Set 1/16 corner south 0.2' at south shoulder of road
	Offset irons N-8 24.75'
2643.8	Set 1/4 stone south 0.4'
	South to shoulder of road 12.5'
	North to shoulder of road 10.0'
2670	Power line
3930	Centerline of highway C.C.
3965.7	Set 1/16 corner south 0.6'
5665.2	Corner stone south 1.0'

SOUTH BET. 16-17 T32
 Var. 0°45'

000

Set section corners 8-9-16-17
 at intersection of roads in south
 ditch on curve.

Pine 16" S3 W 72.7'
 Pine 14" N53E 46.4

120 Leave swamp
 1315 Enter swamp
 1316.4 Set 1/16 corner west 14.1'
 1355 Leave swamp
 1520 Enter swamp
 1700 Leave swamp
 2095 Enter swamp
 2180 Leave swamp
 2632.75 Set $\frac{1}{4}$ stone west 28.25' 6' east
 of drainage between swamps Flows
 north.
 Mounded with stone
 2730 Enter swamp
 3060 Leave swamp
 3414 Centerline of creek flows SE 28'
 across
 3620 Centerline of creek flows west 11'
 across
 3813 Centerline of creek flows east 10'
 across
 3949.15 Set 1/16 corner west 42.4' on top
 of hill
 5265.5 Corner stone west 56.5'
 5291.5 End of rand. line

EAST BET. 16-21 T32

000	5224.9	On rand. line bet. 17-20
305		Centerline of creek
330		Centerline of creek
365		Leave creek flows south
1330.2		Set 1/16 corner north 105.4'
1365		Enter swamp
1537		Centerline of creek 15' wide flows south
1640		Leave swamp
2661.4		Set $\frac{1}{4}$ stone north 130.55' on north side of hill. Mounded with stone
3992.6		Set 1/16 corner north 155.7'
5323.9		Stone section corner 15-16-21-22 north 180.9'

NORTH BET. 19-20 T32

000 Section corner stone
1306.15 Set 1/16 corner on rand. line
at center of road. Offset iron
east 24.75'
2612.3 Set 1/4 stone 0.65' east at centerline
of road as witnessed by two iron
pipes. Offset iron pipe east 24.75'
3938.6 Set 1/16 corner west 6.5'
6' west to shoulder of road
13' east to shoulder of road
Offset pipe west 24.75'
5261.7 Turned left of ford. tan. $77^{\circ}10'$
14.2' to section corner stone
at road intersection

NORTH BET. 17-18 T32

Var. 0° 00'

000	Section corner stone
1319.5	Set 1/16 corner west 0.6'. Two feet to east shoulder of road. Offset iron east 24.75'
2639.0	Set 1/4 stone at centerline of road at old iron pipe west 1.2' Offset iron west 24.75'
3854.9	Offset west 27.3'
3958.5	Set 1/16 corner east 1.15'. Offset iron east 24.75'
5274.5	Turned left NW off ford. tan 82°00' 24.1' to section corner as identified by old iron pipe at intersection of roads and set section corner stone 7-8-17-18 Offset iron pipe west 24.75'

SOUTH BET. 20-21 T32

000 5291.5 On rand. line bet. 16-17
245 Enter swamp
579 Centerline of creek 4' wide
655 Leave swamp
1095 Enter swamp
1215 Leave swamp
1290.4 Set 1/16 corner west 71.6' in
swamp
2395 Centerline of creek 15' wide
flows SE
2606.8 Set $\frac{1}{4}$ stone west 86.7' in low
swampy area. Nothing to witness
Mounded with stone
3070 Enter marsh from beaver dam
3923.2 Set 1/16 corner west 101.8'
4005 Leave marsh and enter balsam
swamp
262.4 Turn left of back tan. to section
corner stone $78^{\circ}56'$ 119.1'

EAST BET. 9-16 T32
Var. 1° 40'

000 Section corner stone at inter-
section of roads.
80 Leave swamp
635 Enter swampy valley brs. N-S
705 Leave swampy valley
1314.9 Set 1/16 corner north 16.65'
1690 Enter swamp
1855 Leave swamp
2629.8 Set $\frac{1}{4}$ stone north 33.3'
North 6' to ash swamp

Ash 9" N4 W 28.1'
Ash 11" N35E 23.7'

2920 Enter swamp
3495 Leave swamp
3805 Enter swamp
3944.7 Set 1/16 corner north 49.95'
1/16 corner 20' north of swamp
4025 Leave swamp
4285 Enter marsh
4426 Creek 3' wide
4665 Leave swamp
5040 Enter swamp
5246.1 End of random line. Turned
left off ford. tan. NE 78° 35'
68.0' to corner stone.

5247.4 intersect N-S random line at
station 35.8'

5246.1
13.5
5259.6
5247.4
29.8

0

WEST BET. 7-18 T32

Var. 5° 00'

000	Section corner stone at inter- section of roads
1321.1	Set 1/16 corner north 16.5'
2642.2'	Set $\frac{1}{4}$ stone north 33.0'
2770	Centerline of power line
3963.3	Set 1/16 corner north 49.5'
4365	Enter swamp
4615	Centerline of highway C.C.
4880	Leave swamp
5091	Enter river
5390	Leave river
5717.9	Section corner stone north 71.7'

EAST BET. 8-17 T32

000.	Section corner stone.
1322.3	Set 1/16 corner south 2.7'
	South to shoulder of road 4'
	North " " " " 16'
	Offset irons N-S 24.75'
2644.65	Set $\frac{1}{4}$ stone south 5.35'
	South to shoulder of road 8'
	North " " " " 14'
	Set stone 1' below top of road.
	Offset irons N-S 24.75'
3967.0	Set 1/16 corner south 8.0'
	North to shoulder of road 16'
	South " " " " 7'
4785	Enter swamp
5289.3	Section corner stone south 10.7
5290.1	End of random line.

NORTH BET.. 8-9 T32

000 Section corner stone.
555 Leave swamp
1315.3 Set 1/16 corner on random
Offset iron east 24.75 in
swamp.
2630.6 Set $\frac{1}{4}$ stone on random. at
center line of road on fence
line.
Offset irons E-W 33.0'
3952.1 Set 1/16 corner east 1.7'.
Offset iron west 24.75'
5273.6 Set section corners 4-5-8-9-
at road intersection 3.4! east.
Set stone 18" below top of road.
Offset iron west 24.75

WEST BET. 5-8 T32
Var. 4.30'

000	Section corner stone at inter- section of roads
1326.6	Set 1/16 corner north 10.4'
2653.2	Set 1/4 stone north 20.75' on west side of hill about one third of the way from the bottom. Nothing to witness. Mounded with four large stone.
2830	Enter swamp
3285	Leave swamp
3979.8	Set 1/16 corner north 31.1'
5306.4	Set section corners 5-6-7-8 north 41.5' at corner of fence- stumps correspond to old witnesses.
	"Tronwood 5" N65W 35.3'
5307.0	Mounded with stone. End of rand. line

WEST BET. 6-7 T32

000 5307.0 On rand. line bet. 5-8
1323.2 Set 1/16 corner north 54.25'
2645.8 Set $\frac{1}{4}$ stone north 67.0' at old
fence corner.
2865 Centerline of power line
3630 Enter swamp
3910 Leave swamp
3965 Centerline of highway CC
3989.8 1/16 corner north 82.90' in high-
way CC. No corner set as road was
being graded. Offset pipe 35' west.
Set location post east 35'.
4075 Enter river on ice.
4550 Leave river
5769.9 Section corner stone 1-6-7-12
north 104.8' as set from rand. line
bet. 7-12 west 60.7' at station
5275.9 at east edge of swamp.

Ash 8" N75E 13.2'
Ash 11" S85W 30.7'

Mounded with stone

NORTH BET. 7-8 T32

Var. 4 30'

000	Section corner stone at inter- section of roads.
1324.5	Set 1/16 corner east 17.1'
1785	Enter low land
2130	Leave low land
2649.05	Set $\frac{1}{4}$ corner east 34.15' at north edge of road-found old pipe corner lying down.
3985	Enter lowland
3973.6	Set 1/16 corner east 51.2'
4220	Leave low land
5298.1	Section corner stone east 68.3'

NORTH BET. 5-6 T32

Var. 2 15'

000	Section corner stone.
1316.4	Set 1/16 corner west 8.5'
2632.8	Set $\frac{1}{4}$ stone west 17.0'. Nothing to witness.
3949.2	Set 1/16 corner west 25.5'
5535.8	Section corner stone west 35.9'

EAST BET. 4-9 T32

000	Section corner stone at intersection of roads.
1303.9	Set 1/16 corner south 0.45' Offset iron south 24.75'
2607.8	Set 1/4 stone south 0.9' at intersection of roads. Offset iron south 24.75'
000	1/4 stone at road intersection.
1313.3	Set 1/16 corner south 3.85' Offset iron south 24.75'
2626.6	Section corner stone south 7.7'

NORTH BET. 4-5 T32

000 Section corner stone at inter-
section of roads.

1320.0 Set 1/16 corner west 2.3'
Offset iron west 24.75'

2640.0 Set $\frac{1}{4}$ stone west 4.65' at center-
line of roads and fence line.
Set iron pipe west 24.75'

3965.0 Set 1/16 corner west 2.8' at
fence line set by county surveyor
in 1914. Offset iron east 24.75'
East to shoulder of road 14'
West to shoulder of road 8'

5606.9 Section corner stone west 0.9'
at intersection of roads.

NORTH BET. 32-33 T33

Var. 5°30'

000	Section corner stone at inter- section of roads.
648	Creek 5' wide flows west
1361.25	Set 1/16 corner west 0.4' Offset iron E-W 24.75' West to shoulder of road 12' East to shoulder of road 13'
2722.5	Set $\frac{1}{4}$ stone at original corner west 0.75'. Offset irons E-W 24.75'
000	$\frac{1}{4}$ stone
1316.1	Set 1/16 corner west 14.4' 16' west of shoulder of road.
2632.2	Set section corners 28-29-32-33 west 28.8' at intersection of roads. Offset irons NW-SE 30'

40

WEST BET. 29-32 T33-6

Var. 2°00'

000	Section corner stone at inter- section of roads.
1315.2	Set 1/16 corner north 2.9' Offset irons N-S 24.75' North to shoulder of road 9.5' South to shoulder of road 15'
2630.4	Set $\frac{1}{4}$ stone north 5.8' Offset pipes N-S 24.75' South to shoulder of road 17' North to shoulder of road 8'.
3728.5	Offset north 25.1'
3945.6	Set 1/16 corner south 16.4' Offset irons N-S 24.75' South to shoulder of road 5' North to shoulder of road 19'
5260.8	Set section corners 29-30-31-32 south 13.6' at centerline of road on fence line. Offset irons N-S 24.75'

WEST BET. 30-31 T33-6

Var. 1 20'

000	Section corner stone
1318.3	Set 1/16 corner stone 19.8' on top of back slope of road on the south side.
1448.3	Offset north 229.9' for triang- ulation of diverted river.
1587	Diverted river
2082	Leave diverted river
2217.8	Hub used in triangulation ; obtained by turning 73 22' between hubs on rand. line from offset at 1448.3
2636.6	Set $\frac{1}{4}$ stone south 39.5' 6' up from toe of dike fill.
	Pine 12" S21E 24.9'
2871	Old river bank
3240	Leave old river
3954.9	Set 1/16 corner south 59.3'
5483.8	Section corner stone set older survey south 82.5'

2
42

NORTH BET. 28-29 T33-6

Var. 2 30'

000 Section corner stone at inter-
section of roads.
270 Enter swamp
695 Leave swamp
1140 Enter swamp
1280 Leave swamp
1358.75 Set 1/16 corner east 8.95' 14'
east of centerline of road.
2717.5 Set $\frac{1}{4}$ stone east 17.9' on center-
line of road to the west on north
shoulder of private drive; 31'
west to centerline of road.
4034.0 Set 1/16 corner east 26.5'-22' east
of centerline of road.
4333.5 Offset east 21.4'
5350.5 Set section corners 20-21-28-29 at
old iron stake on north shoulder
of road on curve. Roads not on
section line. Old iron stake 13.8'
east of rand. line.
Twin Elm 16" N37E 66.4'

EAST BET. 21-28 T33-6

000	Road intersection
17.6	Section corner stone south 6.8'
1342	Fence line
1348.3	Set 1/16 corner south 2.05' 4' south of shoulder of road 21.5' east of old fence line.
2245	Creek 10' wide flows north
2709.7	Set $\frac{1}{4}$ stone 2.7' north at old iron in road. South 7' to shoulder of road. North 16' to shoulder of road. Offset irons N-S 24.75' on fence lines.
4034.9	Set 1/16 corner south 21.75' Offset irons N-S 24.75'
4298.0	Offset south 23.3'
5360.1	Section corner stone south 12.9' at intersection of roads. Offset iron east 24.75'

SOUTH BET. 27-28 T33-6

Var. 3°00'

000	Section corner stone at inter- section of roads.
1321.85	Set 1/16 corner west 2.65' Offset iron east 24.75' Fence line 17' south
2643.7	Set 1/4 stone west 5.3' West to shoulder of road 8' East " " " " 11' Offset irons E-W 24.75'
3965	Set 1/16 corner west 7.95' West to shoulder of road 16' East " " " " 4'
5287.4	Set section corners 27-28-33-34 west 10.6'. 4' west of pipe culvert. 5" below top of ground in ditch on north side of road. Set iron stake at stone 6" out of ground.

WEST BET. 26-35 T33-6

000	Set section corners 25-26-35-36 at intersection of roads. Offset pipe NW 30.0' Offset pipe SE 30.0'
923	Centerline of R.R. track
1329.6	Set 1/16 corner south 1.5' Offset pipes N-S 24.75'
2659.2	Set 1/4 corner stone south 3.0' Offset pipes N-S 24.75'
2693	The east end of the bridge is west 20.0'-at centerline of road Centerline of creek flows south 25' wide
3988.8	Set 1/16 corner north of north shoulder of road 5'
5281.9	End of rand. line
5318.4	Set section corner stone 26-27- 34-35 north at centerline of road. Offset irons N-S 24.75'

346

WEST BET. 27-34 T33-6
Var. 4°30'

- 000 5281.4 On rand. line bet. 26-35
- 1371.15 Set 1/16 corner north 18.35'
South to shoulder of road 3'
North to shoulder of road 18'
Offset irons N-S 24.75'
- 2705.8 Set 1/4 stone north 18.9' at inter-
section of roads.
Offset pipe south 24.75'

- 000 1/4 stone Var. 2 45'
- 270 Enter swamp
- 780 Leave swamp
- 1331.4 Set 1/16 corner 4' south of shoulder
of road. South 8.25'
- 2665.6 End of rand. line
- 2660.5 16.5' south to section corner stone.

WEST BET. 28-33 T33-6

000 2665.6 bet. 27-34 On rand. line
 166 Enter swamp
 1325.05 Set 1/16 corner south 30.25'
 in swamp
 2270 Leave swamp
 2319.4 Offset south 44.8'
 2655.3 Set $\frac{1}{4}$ stone north 0.8' at
 centerline of road
 Offset iron N-S 24.75'
 4" below top of road on big boulder

 Elm 12" NSW 34.3'

 3985.55 Set 1/16 corner south 5.6' at
 centerline of road
 Offset irons N-S 24.75'
 5315.8 Section corner stone south 12.0'
 at intersection of roads.

#848

WEST BET. 14-23 T33-6

000 Section corner stone at center-
line of roads

1337.45 Set 1/16 corner south 5.25'
Offset irons N-S 24.75'

2674.9 Set $\frac{1}{4}$ stone south 10.5' at centerline
of road on fence line.
Offset irons N-S 24.75'

4015.7 Set 1/16 corner south 3.2'
Offset irons N-S 24.75'

5356.5 Section corner stone north 4.1'
Centerline of roads at fence line.

NORTH BET. 35-36 T33-6

000 Section corner stone at inter-
section of roads.

1310 Enter swamp

1316.5 Set 1/16 corner east 0.2'
Offset irons E-W 24.74'
East to shoulder of road 17'
West to shoulder of road 8'

2015.4 Offset west 23.1'

2633.0 Set $\frac{1}{4}$ corner east 23.5' at old
post. East of shoulder of road 15'

3284 Centerline of creek 21' wide
flows SE

3600 Leave swamp

3615 Centerline of R.R. track SE-NW

3953.35 Set 1/16 corner east 21.6'
Offset iron west 24.75'
West to shoulder of road $18\frac{1}{2}$ '
East to shoulder of road 4'

5273.7 Section corner stone east 19.7'

50

SOUTH BET. 31-32 T33-6

Var. 3°

- 000 Section corner stone 29-30-31-32
at centerline of road on fence
line.
- 1321.85 Set 1/16 corner east 44.35'
- 1920 Enter swamp
- 2190 Leave swamp
- 2390 Enter swamp
- 2643.7 Original $\frac{1}{4}$ corner east 88.7'
Set $\frac{1}{4}$ section corner stone

White pine 13" S80E 20.8'
White pine 8" S62W 13.2'

Mounded with stone.
45' east to leave swamp.

- 000 $\frac{1}{4}$ stone Var. 4
- 90 Leave swamp
- 351 Centerline of creek 4' wide flows SW
- 1339.35 Set 1/16 corner west 48.55'
- 1973 Centerline of creek 10' wide flows
west.
- 2678.7 Section corner stone west 97.1'

NORTH BET. 33-34 T33-6

000	Section corner stone
40	Leave swamp
340	Enter swamp
750	Leave swamp
1075	Enter swamp
1105	Leave swamp
1322.95	Set 1/16 corner west 40.05' at east edge of swamp
1430	Enter swamp
1510	Leave swamp
2645.9	Turned left NW off ford. tan 85 42' 80.4' to old stake and set $\frac{1}{4}$ stone.
	Birch 13" N34W 20.6'
	East 50' to centerline of road Mounded with stone
2775	Centerline of road
3000	Enter swamp
3325	Leave swamp
3530	Centerline of road
3973.75	Set 1/16 corner west 141.35' 33' west of centerline of road.
4780	Enter swamp
4938	Leave swamp
5098.7	Turned left NW off ford. tan. to end of rand. line bet. 27-28 43 57' 276.7'

NORTH BET. 20-21 T33-6

Var. 4°30'

000	Section corner stone
1280.05	Set 1/16 corner east 14.8'
2560.1	Old $\frac{1}{4}$ stone 29.6' east at centerline of road
	Offset iron pipes N-S 24.75'
3882.95	Set 1/16 corner east 99.45'
4400	Enter swamp
4970	Centerline of creek 5' wide flows west
5000	Leave swamp
5205.8	Set section corner stone east 169.3' by double proportionate measurement; upon digging found old stake.
5227.5	End of rand. line.

NORTH BET. 34-35 T33-6

000	Section corner stone
590	Enter swamp
1321.25	Set 1/16 corner west 52.8'
1480	Leave swamp
1500	Enter swamp
1845	Leave swamp
2580	Enter ash swamp
2642.5	Old government $\frac{1}{4}$ corner (Iron pipe with brass cap) west 105.6'
2657	Leave ash swamp
3962.0	Set 1/16 corner west 138.45'
5256.7	End of rand. line
5283.5	Section corner stone west 171.3

NORTH BET. 29-30
 Var. N. 3 E.

000 Section corner stone
 1340.45 Set 1/16 corner east 9.3'
 2680.9 Original corner east 18.6' since
 running random line road crew has burned
 original B.T. SE

Oak 14" S49E 53.2'
 Oak 7" N23E 28.2'

Offset irons N-3 24.75'
 000 $\frac{1}{4}$ section stone Var N 4 E
 1311.05 Set 1/16 corner east 16.75'
 2120 Centerline of highway "CC"
 2542 Wisconsin river
 2550.5 Set MC on south shore east 16.85'
 west to road 125'

NORTH BET. 19-20

(Continuing stationing of random line
between 29-30)

- 3475 Leave river
 3933.15 Set 1/16 corner east 25.1'
 22' west to shoulder of road
 Power pole no. 280 north 70.6'
 4147 Centerline of creek flows east
 5244.2 Set $\frac{1}{4}$ stone east 33.5' also
 3.8' west of sta. 2524.4
 Offset pipes E-W 24.75'
 Buried stone at centerline of road
 Power pole no. 285 north 18 east
 92.3'

Then running random line south
bet. 19-20.

- 000 5280.1 on random line bet. 17-18
 1213.3 Set 1/16 corner west 3.5'
 Offset irons E-W 24.75'
 2524.4 $\frac{1}{4}$ stone west 3.8'

NORTH BET. 25-26

000 Section corner stone
1323.7 Set 1/16 corner west 1.5'
2' east to shoulder of road
21' west to shoulder of road
Offset iron east 24.75'
2647.4 Set $\frac{1}{4}$ stone at centerline of roads
west 3.0'
3827 Creek 20' wide flows east
3924.9 Set 1/16 corner west 1.5'
Offset irons E-W 24.75'
4310 Centerline of R.R. track
5320.4 Set section corner stone to sections
23-24-25-26
Offset irons E-W 24.75'

EAST BET. 25-36

000 Section corner stone
1349.6 Set $\frac{1}{16}$ corner south 0.65'
2699.2 Set $\frac{1}{4}$ stone south 1.35'

Elm 6" N75W 46.3'
Mounded with stone

4048.8 Set $\frac{1}{16}$ corner south 2.1'
5310 Enter swamp
5398.4 Section corner stone south 2.7'

58

WEST BET. 23-26
Var. 5°

000 Section corner stone. Enter swamp
1290 Leave swamp
1344.95 Set 1/16 corner south 2.15'
1425 Enter swamp
2689.9 Set 1/4 corner north 13.8'

Spruce 6" S20E 6.4'
Spruce 5" N3E 30.1'

2742 Logging road NW-SE
3290 Logging road NW-SE
3710 Leave swamp
3815 Enter swamp
4034.85 Set 1/16 corner 29.7'
4200 Leave swamp
4330 Enter swamp
900 Leave swamp
5315.4 End of random line

WEST BET. 22-27

000 5315.4 bet. 23-26
 100 Enter swamp
 251 Leave swamp
 625 Enter swamp
 1060 Leave swamp
 1280 Ash swamp
 1407.6 Set 1/16 corner north 79.8'
 1850 Leave ash swamp
 2710 Alders
 2750.95 Set $\frac{1}{4}$ stone north 113.95'
 Elm 14" N43E 40.8'
 Elm 7" N35W 32.5'
 23' west to creek
 10' east to high land
 Not mounded in alders
 2785 Creek 2' wide flows south
 2811 Leave alders
 4094.25 Set 1/16 corner north 148.1'
 5437.5 Section corner stone north 182.2'

NORTH BET. 23-24
Var. 5°30'

- 000 18.1' north of section corner stone
- 1263.4 Set 1/16 corner at centerline of road
- Offset irons E-W 24.75'
- 2544.8 Set 1/4 stone at centerline of road on fence line
- Offset irons E-W 24.75'
- 000 1/4 stone
- 1323.1 Set 1/16 corner
- Offset irons E-W 24.75'
- 2646.2 Section corner stone

NOTE:

Section line and random line are coincident

NORTH BET. 13-14 T33N.

000 Section corner stone
 1323.4 Set $\frac{1}{16}$ corner east 0.5'
 Offset iron west 24.75'
 7.1' west to shoulder of road
 $5\frac{1}{2}$ ' south to centerline of road
 to the east.

2615 Enter swamp
 2646.75 Set $\frac{1}{4}$ stone east 1.0'
 Offset irons E-W 24.75'

3020 Leave swamp
 3969.2 Set $\frac{1}{16}$ corner east 1.5'
 Offset irons E-W 24.75'

5293.5 Set section corners 11-12 2' EAST
 13-14 at intersection of road
 Offset irons south 45 west 50'
 Offset irons north 45 east 25'

62

62

WEST BET. 12-13 T33N
Var. 3°20'

000	Section corner stone
1323.9	Set 1/16 corner south 1.55' Offset irons N-S 24.75'
2647.75	Set 1/4 corner south 3.1' Offset irons N-S 24.75'
3971.6	Set 1/16 corner south 4.65' Offset irons N-S 24.75'
5295.5	Section corner stone 6.2' south

WEST BET. 11-14 T33N

Var. 2° 00'

- 000 Section corner stone
1337.1 Set 1/16 corner north 2.7'
2' south of south ditch of
road.
2674.3 Set $\frac{3}{4}$ stone at centerline of
road north 5.4'
4011.4 Set 1/16 corner north 0.35'
5164.4 End of random line. Set section
corners 10-11-14-15 west 184.2'
and south 4.7'
Offset irons north and south 24.75'

WEST BET. 20-29 T33N

000 Section corner
1315.0 Set 1/16 corner north 42.75'
2629.85 Set 1/4 stone north 85.5'

Ash 6" S48E 5.9'
Twin Ash 14" N74W 8.0'
Mounded with stone

3944.8 Set 1/16 corner north 128.25'
4810 Centerline of highway "CC"
5149.8 Set M.C. north 167.5'

Spruce 22" S40E 23.0'
Tamarac 8" N49E 42.5'

Corner stone 109.9' in river

BET. 5-6 T33N
 (South from $\frac{1}{4}$ stone bet. 5-6)

000 Set $\frac{1}{4}$ post at old $\frac{1}{4}$ post

Power pole no. 346 N64E 23.5'

South to shoulder of road 35'

1311.05 Set 1/16 corner west .33' at
 centerline of road

Power pole 340 S16E 68.4'

2327 Creek 6' wide flows east

2622.1 Set section corner stone to
 sections 5-6-7-8 west .66'
 at centerline of road

Offset irons E-W 24.75'

2643.2 Power pole no. 335 S37E 46.0'

End of random line

(North from $\frac{1}{4}$ stone Bet. 5-6)

000 $\frac{1}{4}$ stone. Enter swamp

2643.9 Set section corner stone to
 sections 5-6-31-32 at original
 location 6.05' east

Tamarac 5" S42E 19.4'

Tamarac 8" N77E 15.5'

Tamarac 5 $\frac{1}{2}$ " N18W 26.6'

Mounded with stone

1326.15 Set 1/16 corner west 3.02'

SOUTH BET. 7-8 T33N

000 2643.2 on random bet. 5-6
1290.85 Set 1/16 corner west 1.0'
Power pole no. 330 S49E 35.3'
East to shoulder of road 19'
West to shoulder of road 6'
Offset irons E-W 24.75'
2066 Creek 4' wide flows east
2601.9 Set 1/4 stone west 1.3'
Offset iron west 24.75'
West to shoulder of road 4'
East to shoulder of road 22'
Power pole no. 325 N73E 31.6'
3912.95 Set 1/16 corner west 1.65'
Offset irons east and west 24.75'
Power pole no. 320 N48E 48.3'
West to shoulder of road 4'
East to shoulder of road 20'
5223.0 Set section corner stone to
sections 7-8-17-18 west 2.0'
Power pole no. 315 N48E 37.0'
Offset irons E-W 24.75'
East to shoulder of road 18'
West to shoulder of road 7'
5284.7 End of random line.

SOUTH BET. 17-18 T33N

000 5284.7 On random bet. 7-8
 1249.35 Set 1/16 corner west 2.3'
 Power pole no. 310 N46E 37.3'
 Offset irons east and west 24.75'
 East 16' to shoulder of road
 West 9' to shoulder of road
 2560.4 Set $\frac{1}{4}$ stone west 2.6'
 West to shoulder of road 10'
 East to shoulder of road 15'
 Power pole no. 305 N30E 63.0'
 Offset irons E-W 24.75'
 3871.35 Set 1/16 corner west 2.9'
 Power pole no. 300 N30E 67.5'
 West to shoulder of road 9'
 East to shoulder of road 16'
 5182.4 Set section corner stone to
 sections 17-18-19-20 west 3.2'
 Power pole no. 295 N20E 80.6'
 Offset irons E-W 24.75'
 East to shoulder of road 16'
 West to shoulder of road 9'
 5280.1 End of random line

68.

WEST BET. 15-22 T33N
Var. 4°45'

000 Section corner stone at fence
lines and centerline of road
Offset irons N-S 24.75'
1336.3 Set 1/16 corner on random line-
(random line and section line
the same)
2672.6 Set 1/4 stone at road intersection
and old iron
Offset one pipe north 24.75'
4012.05 Set 1/16 corner north 28.4'
5351.5 Original section corner north
56.8'

Maple 16" S7E 21.0'

NORTH BET. 21-22 T33N

000	Section corner stone in road
1323.65	Set 1/16 corner Offset irons E-W 24.75'
2647.3	Set $\frac{1}{4}$ stone at road intersection Offset iron north 24.75'
3965.9	Set stone 1.5' below top of road Set 1/16 corner west 0.1'. north and east of fence line
5284.5	Original section corner west 0.2'

NORTH BET. 14-15 T33N

- 000 Section corner stone
- 1332.4 Set 1/16 corner east 27.8'
- 2664.8 Set 1/4 stone east 55.65'
- Elm 8" S82E 29.5'
- Mounded with stone
- 3570 Enter swamp
- 3642 Logging road
- 3664 Leave swamp
- 3997.2 Set 1/16 corner east 83.5'
- 4257 Enter swamp
- 4532 Leave swamp
- 4868 Enter swamp
- 5076 Leave swamp
- 5329.6 Section corner stone east 111.3'

NORTH BET. 7-12 T33N R6-R7

000	Section corner stone at inter- section of roads
	Offset irons SE-SW 34.9'
1325	Set 1/16 corner east 3.4'
	Offset iron east 24.75'
2650.0	Set $\frac{1}{4}$ corner east 6.75'
	along south edge of culvert
	Offset irons E-W 24.75'
	West to shoulder of road 10'
	East to shoulder of road 5'
3975.0	Set 1/16 corner east 10.1'
	On old fence line.
4215.4	Centerline of railroad track
4538	Enter alders
4656	Centerline of creek flows NW
4700	Leave alders
5145	Enter alders
5240	Creek flows NE
5300	Original corner stone east 13.5'

72

72

NORTH BET. 11-12 T33N

000	Section corner
1320	Set 1/16 corner 0.75' west
	Offset one iron west 24.75'
2640	Set $\frac{1}{4}$ stone west 1.5'
	Offset irons E-W 24.75'
	Stone sets in east ditch of old road.
3310	Enter swamp
3960	Set 1/16 corner west 2.25' in swamp
5090	Leave swamp
5279.5	End of random line
5280	Set section corner stone to sections 1-2-11-12 west 3.0'
	Offset irons E-W 24.75'

WEST BET. 1-12 T33N

000	Point 13.5' west of section corner stone
474	Centerline of R.R. track
1325.6	Set $\frac{1}{16}$ corner south 4.1'
2664.7	Set $\frac{1}{4}$ stone south 8.2' at original corner.
885	Enter swamp
1635	Leave swamp
2880	Enter swamp
3050	Leave swamp
3445	Enter swamp
3870	Leave swamp
3982.45	Set $\frac{1}{16}$ corner south 6.75'
4159	Enter swamp
4477	Leave swamp
5300.3	Section corner stone south 5.3'

NORTH BET. 1-2 T33N

- 000 5279.5 On random line bet. 11-12
- 125 Enter swamp
- 1333.1 Set 1/16 corner west 3.975' on old road
- 2665.5 Set $\frac{1}{4}$ stone west 4.95' on old abandoned road
- 3998.3 Set 1/16 corner west 5.9' on old road.
- 5347.3 Set section corners to sections 1-2-35-36 T32-T33 at an old stake on old road .
Offset irons E-W 24.75'

NORTH BET. 1-6 T33N R6-7

000	1.9' east of stone
1319.5	Set 1/16 corner west 56.7'
1515	Leave swamp
2060	Enter swamp
2638.9	Old $\frac{1}{4}$ stone west 111.6' in swamp
3699	Creek 22' wide flows NE
3831	Same creek flows NW
3958.8	Set 1/16 corner west 166.5'
3970	Leave swamp
5102	Centerline of pavement
5277.8	Section corner stone west 221.4'

70

76

WEST BET. 16-21 T33N

000 Section corner stone
1330.3 Set 1/16 corner north 41.8'
2639.8 Turned right NW 76 05' to original
corner 86.2' and set stone

Yellow Birch 13" N6E 22.6'
Mounded with stone. at NE
corner of clearing
Hemlock 11" N55W 26.8'

3925 Enter swamp
3983.35 Set 1/16 corner north 124.2'
5306.1 Set section corner stone to
sections 16-17-20-21 north 164.8'
By double proportionate measurements.
Upon digging found a very old stake.
Nothing to witness.

4948 Leave swamp
5338.1 End of random line and offset north
167.4'

WEST BET. 17-20

000	5338.1	On offset continuing random line bet. 16-21
1292.8		Set 1/16 corner north 11.2' (Set M.C. 780' from $\frac{1}{4}$ corner on the east bank of the Wisconsin river river)
1463		Centerline of highway C.C.
1854		Enter Wisconsin river
2478		Leave Wisconsin river
2616.8		Set $\frac{1}{4}$ stone north 25.7'
3940.8		Set 1/16 corner north 39.85'
5265.8		Section corner stone in road north 54.0' 54.0'

NORTH BET. 15-16

000 Section corner stone
 1322.6 Set 1/16 corner east 36.2'
 2645.2 Set 1/4 stone east 72.4' at north edge
 of large boulder

Maple 8" S46W 29.0'
 Elm S20E 39.7'

2832.9 Offset east 70.3'
 2870 Centerline of highway CC
 3141.2 Turned right N.E. off forward tan-
 gent to original MC corner 37.0'
 27°00' To original cedar BT witness
 to it."

(South from original section corner
 9-10-15-16)

000 Corner in swamp
 240 Leave swamp
 1340.8 Set 1/16 corner east 40.7'
 1772 Enter Wisconsin river.
 2185.6 Original MC corner on south side
 of river east 66.4'

EAST BET. 24-25

000 Section corner stone
331.3 Centerline of R.R. track
1284.25 Set 1/16 corner south 48.4'
1392 Enter swamp
1737 Leave swamp
2568.5 Set $\frac{1}{4}$ stone south 96.75'

Pine stump 14" S55W 57.5'
Pine stump 18" N70E 29.7'
Mounded with stone

3852.75 Set 1/16 corner south 145.1'
in swamp
4200 Enter swamp
4520 Leave swamp
5033 Enter swamp
5137.0 193.5' south to stone corner

NORTH BET. 26-27 T33N

000 Section corner stone
 395 Enter swamp
 495 Leave swamp
 710 Enter swamp
 835 Leave swamp
 950 Enter swamp
 1010 Leave swamp
 1316.75 Set 1/16 corner west 1.55'
 1710 Enter swamp
 2633.5 Set 1/4 stone west 3.1'
 Ash 8" N54E 17.9'
 Ash 10" N32W 10.8'
 3950.25 Set 1/16 corner west 4.65'
 4690 Leave swamp
 5267.0 Set section corners 22-23-26-27
 by double proportionate measurement,
 west 6.2'. North 45.7' at station
 64.4 on random line bet. 22-27
 5327.9 End of random line
 (Witnesses to section corner)
 Pine 12" S17W 67.8'
 Pine Stump 10" S63E 22.5'

On SW side of knoll about 300'
 around. Mounded with stone.

NORTH BET. 22-23 T33N

000 5327.9 bet. 26-27
1255.85 Set 1/16 corner on random line
2572.6 Set $\frac{1}{4}$ stone east 6.3'

Oak 5" N10E 19.1'
Oak 6" S31W 17.3'
Mounded with stone

3709.6 Offset east 29.6'
3889.35 Set 1/16 corner west 17.5'
5206.2 Section corner stone west 10.8'

82

WEST BET. 18-19 T33N

000 Section corner stone
400 Enter swamp
1210 Leave swamp
1238.0 Set 1/16 corner north 1.0'
2476.0 Set 1/4 stone north 2.0'

Elm 11" N56W 51.3'
Elm 26" S9W 29.4'
Mounded with stone

2899 Creek flows SE
2987 Tangent to same creek
3714 Set 1/16 corner north 3.0'
4718 Old road
5110.6 Section corner stone north 4.5'

WEST BET. 6-7 T33N

000	Section corner stone
1200	Low land
1287.4	Set 1/16 corner south 17.4'
1850	Leave low land
2574.8	Set $\frac{1}{4}$ stone south 34.7' on south edge of wood road
	Maple 11" N65W 76.5' Mounded with stone
3100	Old road brs. SE-NW
3862.2	Set 1/16 corner south 52.1' In opening where wood has been cut off.
5194.5	Section corner stone south 70.1'

WEST BET. 7-18 T33N

000 Section corner stone
110 Enter marsh
1270 Leave marsh
1271.0 Set 1/16 corner north 4.4'
1930 Old road SW-NE
2542.0 Set $\frac{1}{4}$ stone north 8.75'

Birch 7" N6W 19.0'
Birch 14" S40E 36.0'

3813.0 Set 1/16 corner north 13.0'
5115.8 Section corner stone north 17.6'

EAST BET. 5-8 T33N

000	Section corner stone
319	Creek 18' wide flows south
1292.87	Set 1/16 corner north 55.0'
2075	Enter marsh
2585.75	Set $\frac{1}{4}$ stone north 110' mounded with stone
3470	Leave marsh
3878.6	Set 1/16 corner north 165.0'
4890	Enter marsh
5163.4	End of random line
5171.5	Old post north 220.05' Identified as original by William Averill and set stone

EAST BET. 4-9 T33N

- 000 Section corner stone
- 480 Leave swamp
- 1326.75 Set 1/16 corner on random line.
Random line and section line
coincident.
- 2653.5 Set $\frac{1}{4}$ stone at road intersection
on random line

- 000 $\frac{1}{4}$ stone
- 700 Enter swamp
- 1330.75 Set 1/16 corner south 36.4'
- 1790 Leave swamp
- 2661.5 Set section corner stone at old
post south 72.8'. Nothing to
witness. Mounded with stone.

WEST BET. 2-35 T33N-T34N

000 Section corner stone in swamp
on old road.

1052 Leave swamp

1323.7 Set 1/16 corner 9.65' north

2647.4 Set $\frac{1}{4}$ stone north 19.3'

Oak 19" N65E 37.2'

3971.1 Set 1/16 corner north 28.95'

5294.8 Set section corner stone to
2-3-34-35 at old iron in old
road.

Oak 11" N12E 22.0'

WEST BET. 3-34 T33N-T34N

000 Section corner stone
518 Centerline of highway CC brs. SSW-NNE
1300 Enter river (Wisconsin) flowage
3100 Leave river " "
3959.25 Set 1/16 corner north 8.1'
5279.0 Set section corner stone north 11.5'
at centerline of road on fence line
Offset irons EW 24.75'
Power pole no. 396 S47W 25.0'

NORTH BET. 4-5 T33N

000 Section corner stone
1316.75 Set $\frac{1}{16}$ corner east 19.35'
2633.5 Set $\frac{1}{4}$ stone at road intersection
38.7' east Offset iron south
24.75'

Elm 12" N34E 73.7'

3901.7 Set $\frac{1}{16}$ corner east in road
74.5' Offset irons EW 24.75'
5163.3 Set section corner stone in road
east 110.1' Offset irons EW 24.75'

WEST BET. 1-36 T33N-T34N

000 Section corner stone
1320.0 Set 1/16 corner north 9.5'
Offset irons NS 24.75'
1471 Creek 12' wide flows WNW
1773 Centerline of R.R. track brs. SSE-NNW
1820 Enter swamp
2080 Leave swamp
2640 Set $\frac{1}{4}$ stone north 19.0' at old iron
stake.
3218 Enter swamp
3962.8 Set 1/16 corner north 30.8' near
east edge of ridge in swamp.
5285.6 Section corner stone north 42.6'

WEST BET. 2-11 T33N

000	North of section corner stone 0.5'
525	Enter swamp
1325.3	Set $\frac{1}{16}$ corner north 7.55'
2650.65	Set $\frac{1}{4}$ stone at old post north 15.6'
3992.75	Set $\frac{1}{16}$ corner north 58.15'
4079	Leave swamp for island
4296	Leave island for swamp
4396	Leave swamp for island
4492	Leave island for swamp
5334.9	Set section corners 2-3-10-11 north 100.7' in open swamp

WEST BET. 3-10 T33N

000	Section corner in swamp
1145	Leave swamp
1338.0	Set 1/16 corner north 17.15'
2676.0	Set 1/4 stone north 34.3' at old 1/4 post
000	1/4 stone
728	Centerline of highway CC
1120	Enter Wisconsin river
1465	Leave Wisconsin river
2652.7	Section corner stone north 13.6'

SOUTH BET. 2-3 T33N

000 Section corner stone
 1322.6 Set 1/16 corner west 6.8'
 (Found old stake)
 1685 Enter swamp
 1810 Leave swamp
 2000 Enter swamp
 2651.85 Set $\frac{1}{4}$ stone west 13.6'

 Tamarac 6" N60E 24.3'
 Spruce 6" S5E 51.9'
 Mounded with stone.
 (Found old stake)

 3205 Leave swamp
 3290 Enter swamp
 3600 Leave swamp
 3977.75 Set 1/16 corner west 20.4'
 4560 Enter swamp
 5303.7 Section corner stone west 27.2'

94

SOUTH BET. 10-11 T33N

000	Section corner stone in swamp
1326.3	Set 1/16 corner west 57.45'
2652.6	Set 1/4 stone west 114.9' at old 1/4 stake
2670	Leave swamp
000	1/2 stone in swamp
1185.3	Leave swamp
1318.3	Set 1/16 corner west 9.6'
2636.6	Section corner stone west 19.2'

NORTH BET. 16-17 T33N

000 Offset east 156.3' at 5227.5 on
 random line bet. 20-21
 1250 Enter swamp
 1301.15 Set 1/16 corner east 70.25'
 1795 Leave swamp
 2412.5 Offset east 131.1'
 2624.0 Set $\frac{1}{4}$ stone west 3.6' at old
 $\frac{1}{4}$ post. Mounded with stone

 000 $\frac{1}{4}$ section stone
 26 Centerline of highway CC
 186 Enter Wisconsin river
 641 Leave Wisconsin river
 1340.2 Set 1/16 corner west 21.25'
 2680.4 Set section corners 8-9-16-17.
 at centerline of road on old
 fence line

N.Pine 8" S26E 39.6'
 N.Pine 13" N32W 43.0'

WEST BET. 10-15 T33N

000 5164.4 On random line bet. 11-14
1521.3 Set 1/16 corner north 1.91'
Offset irons NS 24.75'
2858.5 Set 1/4 stone north 8.45' in road.
Offset irons NS 24.75'
3026 Centerline of highway, CC
3385 Enter Wisconsin river
3837 Leave Wisconsin river
4195.7 Set 1/16 corner north 15.0'
5355 Enter swamp
5532.8 Set section corner stone north 21.6'
at original corner. Mounded with sand.

NORTH BET. 9-10 T33N

000	Original section corner
330	Leave swamp
532	Enter swamp
1032	Leave swamp
1165	Enter swamp
1296.77	Set 1/16 corner west 14.9'
1315	Leave swamp
2593.55	Found old stake lying down west 29.85' and set stone.
	NPine 13" N78E 33.7'
3890.3	Set 1/16 corner west 44.77'
5187.1	Set section corner stone west 58.7'

WEST BET. 9-16 T33N

- 000 Original section corner in swamp
- 565 Leave swamp
- 1114 Enter swamp
- 1338.9 Set 1/16 corner south 8.8' in swamp
- 1530 Ridge in swamp
- 1805 Leave swamp
- 2677.85 Set $\frac{1}{4}$ stone south 17.65'
- 4000 Enter alders
- 4016.8 Set 1/16 corner south 26.4'. 8' east to edge of swamp
- 4210 Centerline of creek 20' wide flows south
- 4268 Leave alders
- 5355.7 Section corner stone south 35.3'

WEST BET. 19-30 T33N

000	Section corner in Wisconsin river.
1265	Set 1/16 corner on random line (Random line and section line coincidental) Offset irons NS 24.75'
2530	Set $\frac{1}{4}$ stone. Offset irons NS 24.75'
3795	Set 1/16 corner. Offset irons NS 24.75'
5243.2	Section corner stone at centerline of road.

NORTH BET. 7-12 R5-R6 T32

000	5281.5 on random line bet. 8-13
545	Creek (dry) flows E-W
1316.87	Set 1/16 corner west 42.0'
1860	Creek (dry) flows E-W
2636.56	Set $\frac{1}{4}$ stone west 48.22'
	On high point. Mounded with sand.
3956.23	Set 1/16 corner west 54.47'
4514	Creek one foot wide
4720	Leave creek
5275.9	Section corner stone west 60.7'
5299.3	End of random line

NORTH BET. 1-6 R5-R6- T32

000 5299.3 On random line bet. 7-12
1298.27 Set 1/16 corner west 67.95'
2617 Set $\frac{1}{4}$ stone west 73.2'

Elm 6" S60W 14.8'

Mounded with sand
3937.6 Set 1/16 west 79.45'
4432 Creek five feet wide flows east
4760 Enter cedar swamp
5170 Leave cedar swamp
5413.7 Section corner stone west 86.4'
(Original)

102

NORTH BET. 8-9 T33N

000 2678.8 On random line bet. 16-17
Offset west 30.3'
1323.87 Set 1/16 corner east 15.1'
1325.9 Offset east 30.3'
2067 Centerline of creek 45' wide
flows east
2647.75 Set $\frac{1}{4}$ stone east 12.1'

Jack pine 6" N42W 23.2'
Tamarac 8" S35E 32.5'
3971.62 Set 1/16 corner east 39.4'
5295.5 Section corner stone east 66.7'

NORTH BET. 3-4 T33N

000 Section corner stone
1325.95 Set $\frac{1}{16}$ corner east 8.1'
2651.9 Set $\frac{1}{4}$ stone in road east 16.2'
at fence lines and iron spike
at turn in road.

SOUTH BET. 3-4

000 Section corner stone on town line
1326.05 Set $\frac{1}{16}$ corner west 3.4' in road
Offset irons E-W 24.75'
2652.1 Section corner stone west 6.8'

104

EAST BET. 4-33 T33-T34

000 Section corner in road. Enter
lowland
1313.55 Set 1/16 corner north 1.15'
2627.1 Set $\frac{1}{4}$ stone north 2.3'

Oak 12" S53W 12.9'
Soft Maple 11" N70E 19.7'

Mounded with stone
2750 Leave lowland
3680 Enter swamp
3890 Leave swamp
3940.65 Set 1/16 corner north 5.2'
5254.2 Set section corner stone north 4.6'

EAST BET. 5-32 T33-T34

000	Original section corner in swamp
1100	Leave swamp
1325.55	Set $\frac{1}{16}$ corner north 21.9'
2651.1	Set $\frac{1}{4}$ corner north 43.8' (Original)
3972.6	Set $\frac{1}{16}$ corner north 50.75'
4300	Offset south 28.6'
5294.1	Section corner stone north in road 86.3'. Offset irons EW 24.75'

EAST BET. 6-31 T33-T34

000 Section corner stone in swamp
1345.95 Set 1/16 corner south 3.0' in
swamp
2165 Leave swamp
2662.4 Set $\frac{1}{4}$ stone south 5.95'.
Mounded with stone
3978.85 Set 1/16 corner south 8.9' in
low ground
5070 Enter swamp
5295.3 Original corner south 11.8' set
stone.

Tamarac	5"	S42E	19.4
Tamarac	8"	N77E	15.5
Tamarac	5 $\frac{1}{2}$ "	N18W	26.6

Mounded with stone

WEST BET. 8-17 T33N

000 Section corner stone at center-
line of road and fence line
1294.27 Set 1/16 corner south 47.5'
2370 Enter swamp
2588.55 Set $\frac{1}{4}$ stone south 95.0'

North to swamp 24'
West to swamp 20'

Nothing to witness; mounded
2685 Leave swamp
3882.82 Set 1/16 corner south 142.5'
5177.1 Section corner stone south 190.0'

SOUTH BET 1-6 T33 R5-R6

000 Turned left off back tan. 16° 00'
21.8' to original Township corner

Spruce 4" S70W 23.6'

1125 Leave swamp

1298.3 Set 1/16 iron east 0.15'

2425 Enter swamp

2610.3 Set a cedar location post for $\frac{1}{4}$
corner east 2.6' in soft wet swamp.
Nothing to witness

2850 Creek 10' wide flows east

3040 Leave swamp

3931.3 Set 1/16 iron east 5.1'

5252.3 Set section corner stone to
sections 1-6-7-12 east 7.55'.
Blaze line to it, at what appears to have
been an old camp site.

Maple 5" N1W 32.6'

Maple 8" S32W 51.5'

Elm 8" S26E 92.5'

Elm 5" N44E 68.2'

5276.2 End of random line.

SOUTH BET. 7-12 T33 R5-R6

000 5276.2 on random line bet. 1-6
 1125 Enter low grassy meadow
 1297.1 Set 1/16" iron east 10.0'
 1440 Dry creek 6' wide flows SE
 1585 Leave low grassy meadow
 2565.0 Turned left (SE) off forward tan.
 to original $\frac{1}{4}$ section corner and
 set $\frac{1}{4}$ section stone in low wet spot.
 13° 12' 54.6'

Elm 6" N3'
 Elm 8" S60W 19.1'
 Elm 8" N15E 41.0'

3943.2 Set 1/16 iron east 1.2'
 4515 Old logging road
 5070 Old logging road
 5267.8 Turned left off forward tan.
 85° 51' 5.9' to original corner
 identified by live original witness.
 Then offset random line 4.8' to
 avoid cutting original B.T..
 Set section stone to sections
 7-12-13-18

Maple 5" N22W 35.8'
 Maple 9" N70E 65.6'

Original maple B.T. 22" S17W 17.6'
 Original maple B.T. 23" S67 $\frac{1}{2}$ E 24.0'
 Mounded with stone

SOUTH BET. 13-18 T33 R5-R6

000 5267.8 On random line between 7-12
1318.2 Set 1/16 iron west 16.3'
2635.85 Set 1/4 stone west 33.7'

Ash 7" S69E 28.3'
Elm 8" S67W 34.9'
SW to centerline of creek 50'

3080 Creek 3' wide flows SE
3953.5 Set 1/16 iron west 50.55'
5271.2 Set section corner stone to sections
13-18-19-24 west 67.4'

Maple 14" N18W 74.9'
Mounded with stone

5271.7 End of random line.

SOUTH BET. 19-24 T33 R5-R6

000 5271.7 On random line bet. 13-18
 1317.7 Set 1/16 iron west 84.5'
 2513 Old road
 2517 Enter swamp
 2634.85 Set $\frac{1}{4}$ stone west 101.65' near
 center of swamp.

Pine stump 18" West (in swamp)
 80.6'. Mounded with stone
 2970 Leave swamp
 3735 Enter swamp
 3952.5 Set 1/16 iron west 118.8'
 4850 Leave swamp
 5244.9 End of random line. Set section corner
 stone to sections 19-24-25-30,
 south 25.3' and west 135.9' at
 centerline of C.T.H. "E" set stone
 12" below top fo road. Set a
 location post north 23.0'-nothing
 to witness.

SOUTH BET. 25-30 T33 R5-R6

000 5244.9 on random line bet. 19-24
 20 Centerline of C.T.H. "E"
 1345.7 Set 1/16 iron west 153.05'
 2026 Creek 10' wide flows east.
 2666.1 Set $\frac{1}{4}$ stone in low swampy ground
 west 170.2'. North to leave swamp
 68'

 Pine stump 22" N66W 53.6'

 3986.5 Set 1/16 iron west 187.4'
 4053 Boulder 12' by 15', 4' above ground
 5306.95 Set stone to section corners
 25-30-31-36 west 204.55' on south
 side of hill. South to swamp 78',
 nothing to witness. Mounded with
 stone.
 5313.4 End of random line.

SOUTH BET. 31-36 T33 R5-R6

000 5313.4 On random line between 25-30
 310 Enter swamp brs. E-W
 420 Leave swamp
 1300 Top of ridge E-W
 1314.0 Set 1/16 iron west 221.7'
 2500 Centerline of dry creek 6' wide
 flows east
 2634.4 Set $\frac{1}{2}$ stone west 238.9'

Oak 7" N49E 17.2'
 Maple 6" S14W 33.6'
 Mounded with stone.

2653.1 Offset west 301.8'
 3815 Dry creek 5' wide flows east.
 3954.8 Set 1/16 iron east 45.75'
 5202.1 Turned left off forward tan. $21^{\circ}21'$
 78.5' to original Township corners.

Original B.T. stump N1E 31.7'
 Set Township corner stone on
 steep slope.

Hemlock 15" S40E 19.1'
 Cedar 22" N64 $\frac{1}{2}$ E 46.5'
 Mounded with stone.