



Merrill Wis. Jan 21/1929

Mr. O. Poppal. This is a copy of a survey I made Jan 16-1900/1929 for you. I extended the center line of Pier St. South of 1st St. 635 ft. which place I called the corner of Sections 11-12-13 & 14 T. 31 R. 6 E. From this approx. sec. cor. I measured eastward to an intersection with the continuation of a line between the iron at the NW corner of the SW 1/4 NE 1/4 and the stone at the center of Sect. 13 and at 1/2 of this distance which was 1345 1/2 ft. I set a stake on the ice which stake is about on the 1/2 line between the E and W 1/2 of the NW 1/4, then I measured from the stone at the center of Sect. 13, West to the stone at the 1/4 corner and at 1/2 the distance which was 1334 ft I set a stake for the 1/2 corner. then with a transit I ran from the last mentioned 1/2 Cor. to the stake set on the ice. then approx. at the south line of your bond where it intersects with the 1/2 line I turned 90° to the East and at 419.1 ft. and at 1/2 419.1 ft. I set stakes and at these points I turned 90° to the North and called these two lines your East and West lines. Sunday Jan 20. I went back and found two iron pins which Mr. Kehler said have been in a long number of years and always assumed to be on the 1/2 line and which evidently was taken as the 1/2 line when measuring out your description the iron pins are 4.7 ft. West of where I made the 1/2 line thus showing the your lines as we measured them 4.7 ft. = (4 8 3/4") West of where we put them.

Yours
Alex. Deleylie.

G.L. 5 13-31-6
(NE NW)

RECEIVED FROM M
CITY ENGR. 8, 23, 73

Stone
at 1/4 Cor
Sec. 13-14

1334

1334

Stone of
CTR. Sec.

B

(C-59)