Attachment to Tie Sheet C-21, T33N, R7E 43307022000

I visited the corner on 7/09/2019 to verify the corner and reference tie monumentation. I found the Berntsen Monument and all 4 ties from the Michael Oestreich tie sheet (02/01/2008). The established Coordinates and ties agree with existing monument.

Anthony R. Dallman, PLS-2405

Lincoln County Surveyor

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

Note: This form is intended and designed to fulfill all requirements of the Wisconsin Administrative Code, Chapter A-E 7.08 U.S. Public Land Monument Record (3)(a)(b)(c)(d)(e)(f)(g)(h)(i). An additional sheet may be added if necessary to confrom with said requirements.

(a) CORNER LOCATION:

COORDINATES

east quarter corner Section 2

North:

Township 33 North

East:

Range 7 East Town of Birch

Control Station:

County of Lincoln

Latitude: Longitude:

Datum Method

(b) HISTORY OF ORIGINAL CORNER ESTABLISHMENT

SECTION 2

Original Surveyor: J.L. Prentice

Original B.T.'S

Date of Survey: Commenced October1854

Pine 20" dia., N57°W 15 links

Completed October 1854

Pine 16" dia., S57°E 57 links

(f)(g)(h) DESCRIPTION OF MONUMENT FOUND AT THIS CORNER AND IF IT WAS ACCEPTED, STATE ALL EVIDENCE (MATERIAL, TESTIMONIAL, OCCUPATIONS, PLATS, RECORDS, OTHER MONUMENTS) USED AS A BASISFOR ESTABLISHING LOCATION. IF NOT ACCEPTED OF IF NOTHING WAS FOUND, STATE EVIDENCE USED AS BASIS FOR ESTABLISHING LOCATION. IF REESTABLISHED THROUGH LOST CORNER PROPORTIONATE METHODS, INDICATE ALL MONUMENTS, DISTANCES AND DIRECTIONS USED TO ESTABLISH. INDICATE TYPE OF MONUMENT AND SIGN POST FOUND OR SET.

Original surveyor: J.L. Prentice, south corrected at 38.55 chains set quarter section post for sections 1 & 2

Owens-Illinios: June 1954, found granite post lying on road bank. They show a fence to the east, and measurements to section corner to south 40.055 chains and measurement to CW 1/16 corner of Section 1, 19.94 chains.

Michael L. Oestreich: February 2007, found no evidence of granite post mentioned by Owens-Illinois. I set one-quarter at intersection of fence from the east extended to centerline of Grundy Road, and checked the measurements to the section corner to the south: OSM-2645.55' (O & I - 40.055 chains, 2643.63') and CW 1/16 corner of Section 1: OSM-1314.54 (O & I -19.94 chains, 1316.04') I set a Berntsen aluminum monument on 9/14/07 and made witness ties as shown in the plan below. See Map No. 07-02 by Oestreich Surveying & Mappipng, LLC, dated 2/02/07, for complete subdivision of Section 2.

(c)(d)(e) PLAN VIEW OF CORNER WITH TIES TO AT LEAST 4 WITNESS MONUMENTS. IF IN DISAGREEMENT WITH PREVIOUSLY ESTABLISHED CORNER, SHOW THE DISTANCE BETWEEN THE TWO CORNERS AND ALSO INDICATE THE TIES TO THE DISPUTED CORNER.

