U.S. PUBLIC LAND SURVEY MONUMENT RECORD

Note: This form is intended and designed to fulfill all requirements of Wisconsin Administrative Code, Chapter A-E 5.02, U.S. Public Land Survey Monument Record (3)(a)(b)(c)(d)(e)(f)(g)(h)(i). An additional sheet may be added if necessary to conform with said requirements. (a) Corner location: Township 33 North
(d) corner location. Township 33 North
Range7East
Town/City/Village BIRCH
County LINCOLN
Section 21
(b)(f)(g)(h) Description of monument found at this corner and if it was accepted, state all evidence (material, testimonial, occupational, plats, records, other monuments)used as a basis for accepting. If not accepted or if nothing was found, state evidence used as basis for establishing location. If reestablished through lost corner proportionate methods, indicate all monuments, distances and directions used to establish.
WE FOUND A 6" \times 6" Granite stone at the intersection of a fence line running east, south, and north. The stone was found ± 4 feet off the centerline of an existing logging road. We held the stone as best evidence of the west 1/4 corner of section 21.
(c)(d)(e) Plan view of corner with ties to at least 4 witness monuments. If in disagreement with previously established corner, show the distances between the two corners and also indicate the ties to the disputed corner. RECEIVED AT LINCOLN COUNTY COURTHOUSE THIS 14 TH DAY WOODS OF October 20 02 WOODS WOODS WOODS OF October 20 02 WOODS WOODS OF October 20 02 WOODS OR ONTROL POINTS AS SUPPLIED BY
6" MAPLE 12" SPRUCE 8" MAPLE 8" MAPLE 10
EAST 1/4 CORNER SECTION 21 - SECTION CORNER S81°37'32"E N89°41'11"E S81°37'32"E LOGGING ROAD FIELD SAST 1/4 CORNER SECTION 21 - SECTION CORNER - SEC
8" MAPLE NORTH N= 177067.1728 E= 407446.9388
(i) I, Thomas A. Radenz, RLS certify that the corner location on this record was determined by me or under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.