This form is intended and designed to fulfill all requirements of Wisconsin Administra Public Land Survey Monument Record (3) (a) (b) (c) (d) (e) (f) (g) (h) (i). An additional s conform with said requirements. Corner location: Township35North Range8East TownHarrison County _Lincoln	sheet may be added if necessary to
Range 8 East	
1	+
ounty Lincoln	
5 1.	Section 6
(f) (g) (h) Description of monument found at this corner and if it was a (material, testimonial, occupational, plats, records, other monuments) use not accepted or if nothing was found, state evidence used as basis reestablished through lost corner proportionate methods, indicate all directions used to establish.	ed as a basis for accepting. If
August 1864, James Nowlin set post for 1/4 corner at of section corner to the north: 15" Y. Pine, S80°W, 8 links (5.28') 15" Y. Pine, S71°E, 8 links (5.28') April 6, 1988 Milo E. Stefan found a 6" x 6" x 12" r mound of stone with fence line West and South. Al recover the notes of the restoration of this corne it is a stone as set by Francis X. Fuchs in the 19 stone as the perpetuated 1/4 corner and make new r	red granite stone in though I did not er in the courthouse,
 (d) (e) Plan view of corner with ties to at least 4 witness monuments. If in diestablished corner, show the distances between the two corners and a disputed corner. 6" x 6" x 12" Red Granite monument in mound of stone 	isagreement with previously also Indicate the ties to the
2. 8" Red Oak, N64°E, 28.84 feet (1/4S BT) 3. 8" Red Oak, S78°E, 22.30 feet (1/4S BT) 4. 10" Red Oak, S21°W, 4.25 feet (1/4S BT) 5. 8" Red Oak, N09°W, 13.43 feet (1/4S BT) 6. Fence corner, West, 1.0 feet	
(BTs scribed accordingly) Distances to nail in side of trees	
* * *	× 2
	/ *
	* * *
I. Milo E. Stefan	*
(lype or print name) certify that the corner location on this record was determined by me or under my direction and control and that this U.S. Public Land Supply Mar.	ECONSID G

4/27/88

Date









